



PMX-245



Features

- Printing speed: Min 50.8mm/s, Max 127mm/s
- Paper width: 80mm
- Thermal sensitive resistance, photoelectric sensor
- Support Serial+USB+Lan interface
- Labels peel off, tear off automatically
- Memory: DRAM: 4M NV FLASH: 4M
- Support PDF417, QR CODE, DAMATRIX 2D Printing
- Embedded with internet default IP
- 100MB Ethernet interface connection, data transfer



Specifications

Printing method	Direct Thermal
Printing width	16~82mm
Printing speed	127mm/s. (Max.); 50.8mm/s. (Min.)
Dot Density	203dpi(8dots/mm)
Character size (WxH)	Font A: 12 × 24 dots / Font B: 9 × 17 dots Simplify/Traditional/Japanese/Korean: 24 × 24dots
Print Character	ANK Character
Language	English/Japanese/Korean/ Simplify Chinese/ Traditional Chinese
Interface	Serial+USB+Lan interface
Memory	DRAM: 4M; FIASH: 4M
Image	Monochromatic PCX, BMP image files can be load to FLASH, DRAM
Reliability	100Km
Power Supply	DC 24V, 2.5A
Media Type	Paper roll, sticker, Label fold, etc.
Paper exists detection	Photoelectric sensor
Media Diameter	25-85mm
Paper off type	Tear off & peel off
Enlargement & rotation	1to10 times enlargement in both direction; 0°, 90°, 180°, 270° rotation
Temperature	5~45℃
Paper thickness	0.06~0.08mm
Dampness	20~80%RH
Barcode	CODE128、EAN128、ITF、CODE39、CODE93、EAN13、EAN13+2、EAN13+5、EAN8、EAN8+2、EAN8+5、CODABAR、POSTNET、UPC-A、UPCA+2、UPCA+5、UPC-E、UPCE+2、UPC-E+5、CPOST、MSI、MSIC、PLESSEY、ITF14、EAN14
Driver	Win9x/WinME/ Win2000/WinNT/ WinXP, compatible with EPSON,SAMSUNG
Print Command	Compatible with ESC/POS
Dimensions (WxDxH)	220(L) × 148(W) × 150(H) mm
Gross weight	1.44 kg